

SECTION 01580

PROJECT IDENTIFICATION AND SIGNS

PART 1 - GENERAL

1.1 Summary

A. This Section includes basic requirements for temporary Project identification and informational signs required during construction.

B. Related Work Specified Elsewhere

SubmittalsSection 01330

1.2 Quality Assurance

A. Design sign and structure to withstand wind and environmental conditions of locality. Provide with finish adequate to withstand weathering, fading, chipping, and peeling for duration of construction.

1.3 Submittals

A. Submit as specified in Section 01330.

B. Includes, but not limited to, the following

1. Shop Drawings and product data as applicable.
2. Show content, layout, lettering, colors, structure, and foundation.

PART 2 - PRODUCTS

2.1 Identification Signs

A. Project Identification

1. Construct to design, size, and material indicated.
2. Construct structure and framing of wood, structurally adequate to resist design requirements of locality.

3. Construct sign surface of minimum 3/4-inch thickness exterior grade plywood with medium density overlay. Panels shall be of size to minimize joints. Overall size shall be 4' x 8'.
4. Rough hardware shall be galvanized or aluminum.
5. Coating: Paint as specified of colors selected by Engineer.
6. Information Content:
 - a. Project title, logo, and name of Owner as shown on Contract Documents.
 - b. Names and titles of authorities.
 - c. Name and title of Engineer.
 - d. Name of prime Contractor and major Subcontractors.

B. Contractor Identification: If not part of Project identification sign, provide and install Contractor's standard sign.

2.2 INFORMATIONAL SIGNS

A. Construction

1. This includes signs for traffic, construction workers, and general public in regards to directions, warnings, hazards, locations of areas, facilities, equipment, and others of a similar nature.
2. Provide signs of design, size, color, and lettering as required by regulatory agencies. Signs shall be painted metal, wood, plastic, or fiberglass and of materials suitable for the conditions in which they are placed, such as weathering and fading.
3. Construct structure and framing of wood or metal, structurally adequate to resist design requirements of area of Project.

PART 3 - EXECUTION

3.1 Installation

A. Project and Contractor Identification Sign

1. Install in appropriate location so as not to obstruct traffic, pedestrians, or construction operations.
2. Erect on framing or foundation, and rigidly brace.
3. Maintain sign in good repair, in a clean and neat condition.
4. Remove upon completion of Project.

B. Informational Signs

1. Install at appropriate locations and in sufficient quantities to assure visibility. Relocate as required by progress of Work.
2. Maintain signs in good repair, in a neat, clean, readable condition.
3. Remove all signs, framing, supports, and foundations upon completion of Project.

PART 4 - MEASUREMENT AND PAYMENT - Not Applicable.

**** END OF SECTION 01580 ****